ESXPRT000001 - INOX PROTECT

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 1/11

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: ESXPRT000001
Product name INOX PROTECT
Chemical name and synonym Inox Protect

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Protective for stainless steels

1.3. Details of the supplier of the safety data sheet

Name NITTY-GRITTY S.R.L.
Full address via dei Marmorari 36
District and Country 41057 Spilamberto (Mo)

Italia

Tel. 059785210 Fax 0597861612

e-mail address of the competent person

1.4. Emergency telephone number

For urgent inquiries refer to ITALY: 06/3054343 06/49970698

BELGIUM: 070 245 245 CROATIA: +385 1 2348 342

CZECH REPUBLIC: +420 224 919 293

FINLAND: 09 471977 GERMANY: +49 228 287 3211 HUNGARY: +36 80 20 11 99

IRELAND: 01 8092566 or 01 8379964

NORWAY: 22 59 13 00 PORTUGAL: 808 250 143 RUSSIAN: (495) 628 1687 SLOVENIA: + 386 41 650 500 SWEDEN: +46 8 33 12 31 UNITED KINGDOM: 111 AUSTRIA: +43 1 406 43 43 BULGARIA: +359 2 9154 409 DENMARK: +45 82 12 12 12 ESTONIA: 16662, (+372) 626 93 90 FRANCE: + 33 (0)1 45 42 59 59 GRECEE: +30 10 779 3777 ICELAND: +354 525 111 NETHERLANDS: 030 274 88 88 POLAND: (12) 411 99 99 ROMANIA: 021.318.36.06 SLOVAKIA: +421 2 5477 4166 SPAIN: + 34 91 562 04 20

TURKEY: 0 800 314 7900

# **SECTION 2. Hazards identification.**

# 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

ESXPRT000001 - INOX PROTECT

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 2/11

# 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words: Danger

Hazard statements:

**H222** Extremely flammable aerosol.

**H229** Pressurised container: may burst if heated.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**P211** Do not spray on an open flame or other ignition source.

**P251** Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients.**

### 3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification. Conc. %. Classification 1272/2008

(CLP).

1-METHOXY-2-PROPANOL

CAS. 107-98-2 15 - 16,5 Flam. Liq. 3 H226, STOT SE

3 H336

EC. 203-539-1

INDEX. 603-064-00-3

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures.**

# NITTY-GRITTY S.R.L. Revision nr. 1 Dated 17/09/2015 Printed on 17/09/2015 Page n. 3/11

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

### 5.1. Extinguishing media.

# SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture.

# HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

# 5.3. Advice for firefighters.

# GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6. Accidental release measures.**

# 6.1. Personal precautions, protective equipment and emergency procedures.

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

ESXPRT000001 - INOX PROTECT

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 4/11

Do not disperse in the environment.

6.2. Environmental precautions.

### 6.3. Methods and material for containment and cleaning up.

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

# 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage.**

### 7.1. Precautions for safe handling.

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

# 7.2. Conditions for safe storage, including any incompatibilities.

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C/122°F, away from any combustion sources.

# 7.3. Specific end use(s).

Information not available.

# SECTION 8. Exposure controls/personal protection.

# 8.1. Control parameters.

Regulatory References:

DEU DNK ESP	Deutschland Danmark España	MAK-und BAT-Werte-Liste 2012 Graensevaerdier per stoffer og materialer INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
HUN	Magyarország	50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values,

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 5/11

ESXPRT000001 - INOX PROTECT

AF 2011:18

SWE Sverige EU OEL EU

Occupational Exposure Limit Values, AF 2011:18

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC;

Directive 2000/39/EC.

TLV-ACGIH ACGIH 2014

1-METHOXY-2-PROPAN	NOL						
Threshold Limit Value.							
Туре	Country	TWA/8h	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	370	100	740	200		
MAK	DEU	370	100	740	200		
TLV	DNK	185	50				
VLA	ESP	375	100	568	150	SKIN.	
VLEP	FRA	188	50	375	10	SKIN.	
WEL	GRB	375	100	560	150	SKIN.	
AK	HUN	375		568			
TLV	ITA	375	100	568	150	SKIN.	
OEL	NLD	375		563		SKIN.	
MAK	SWE	190	50	300	75	SKIN.	
OEL	EU	375	100	568	150	SKIN.	
TLV-ACGIH		184	50	368	100		

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

# 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

# HAND PROTECTION

None required.

# SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

# EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

# RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

# ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

ESXPRT000001 - INOX PROTECT

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 6/11

# **SECTION 9. Physical and chemical properties.**

# 9.1. Information on basic physical and chemical properties.

Appearance Not available. Not available. Colour Odour Not available. Odour threshold. Not available. Not available Melting point / freezing point. Not available. Initial boiling point. Not applicable. Boiling range. Not available. Flash point. Not applicable. Evaporation rate Not available. Flammability (solid, gas) Not available. Lower inflammability limit. Not available. Not available. Upper inflammability limit. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. 0,695 Kg/l Solubility Not available. Partition coefficient: n-octanol/water Not available. Auto-ignition temperature. Not available. Decomposition temperature. Not available. Not available. Viscosity Explosive properties Not available. Oxidising properties Not available.

### 9.2. Other information.

Information not available.

# SECTION 10. Stability and reactivity.

# 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHOXY-2-PROPANOL: absorbs and disolves in water and in organic solvents, dissolves various plastic materials; it is stable but with air it may slowly form explosive peroxides.

# 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

# 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

1-METHOXY-2-PROPANOL: can react dangerously with strong oxidising agents and strong acids.

ESXPRT000001 - INOX PROTECT

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 7/11

### 10.4. Conditions to avoid.

Avoid overheating.

1-METHOXY-2-PROPANOL: avoid exposure to the air.

### 10.5. Incompatible materials.

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

1-METHOXY-2-PROPANOL: oxidising agents, strong acids and alkaline metals.

# 10.6. Hazardous decomposition products.

Information not available.

# **SECTION 11. Toxicological information.**

According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This product may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.

### 11.1. Information on toxicological effects.

1-METHOXY-2-PROPANOL: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

1-METHOXY-2-PROPANOL LD50 (Oral).5300 mg/kg Rat LD50 (Dermal).13000 mg/kg Rabbit LC50 (Inhalation).54,6 mg/l/4h Rat

# **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

# 12.1. Toxicity.

Information not available.

# 12.2. Persistence and degradability.

1-METHOXY-2-PROPANOL

Solubility in water.

mg/l 1000 - 10000

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 8/11

# **ESXPRT000001 - INOX PROTECT**

Rapidly biodegradable.

# 12.3. Bioaccumulative potential.

1-METHOXY-2-PROPANOL

Partition coefficient: n- < 1 octanol/water.

12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

# **SECTION 13. Disposal considerations.**

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information.**

# 14.1. UN number.

ADR / RID, IMDG, 1950

IATA:

# 14.2. UN proper shipping name.

ADR / RID: AEROSOLS,

FLAMMABLE

IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es).

ESXPRT000001 - INOX PROTECT

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 9/11

IMDG: Class: 2

Label: 2.1

Label: 2.1

IATA: Class: 2 Label: 2.1

Class: 2



14.4. Packing group.

ADR / RID:

ADR / RID, IMDG,

IATA:

14.5. Environmental hazards.

ADR / RID: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: --Limited

Quantities 1 L restriction code (D)

Tunnel

Packaging

Packaging

203

instructions:

instructions: 203

Special Provision: -

IMDG: EMS: F-D, S-U Limited Quantities 1 L

IATA: Cargo: Maximum

quantity: 150 Kg

Maximum quantity: 75 Кg

A145, A167,

Special Instructions:

A802

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Pass.:

Information not relevant.

# **SECTION 15.** Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None.

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

ESXPRT000001 - INOX PROTECT

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 10/11

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

# 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Aerosol 1 Aerosol, category 1
Aerosol 3 Aerosol, category 3

Flam. Liq. 3 Flammable liquid, category 3

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H226 Flammable liquid and vapour.H336 May cause drowsiness or dizziness.

# LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level

Revision nr. 1

Dated 17/09/2015

Printed on 17/09/2015

Page n. 11/11

# ESXPRT000001 - INOX PROTECT

- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.